

# Oilgear Open Loop Pumps At A Glance

Maximum pressure bar/ psi	rated continuous pressure										theoretical displacements [ml/rev] / [in <sup>3</sup> /rev]														frame size	speed	face mounting	dual pump option	side port	rear port	tank mounting				
	450/ 6500	420/ 6000	350/ 5000	275/ 4000	260/ 3750	240/ 3500	210/ 3000	175/ 2500	105/ 1500	Model	11/ .67	14/ .86	22/ 1.36	25/ 1.52	34/ 2.06	48/ 2.82	65/ 3.96	75/ 4.6	100/ 6.0	130/ 7.94	140/ 8.60	200/ 12.20	250/ 15.26	270/ 16.48								370/ 22.58	440/ 26.86	540/ 32.96	Rated RPM
293/4250					260					PVM-011																			A	3600	SAE "A" 2-Bolt	x	x	x	x
400/5800			350							PVWH-04																			A	3000	SAE "A" 2-Bolt	x	x	x	x
293/4250					260					PVM-014																			A	3600	SAE "A" 2-Bolt	x	x	x	x
310/4500				275						PVWH-06																			A	3000	SAE "A" 2-Bolt	x	x	x	x
293/4250					260					PVM-022																			A	3600	SAE "A" 2-Bolt	x	x	x	x
240/3500								210		PVWH-10																			A	3000	SAE "A" 2-Bolt	x	x	x	x
400/5800			350							PVWH-11																			B	3000	SAE "B" 2-Bolt	x	x	x	x
293/4250					260					PVM-034																			B	2400	SAE "B" 2/4-Bolt	x	x	x	x
275/4000						240				PVWH-15																			B	3000	SAE "B" 2-Bolt	x	x	x	x
293/4250					260					PVM-046																			B	3000	SAE "B" 2/4-Bolt	x	x	x	x
206/3000								175		PVWH-20																			B	2400	SAE "B" 2-Bolt	x	x	x	x
400/5800			350							PVG-048																			B	2700	SAE "B" 2/4-Bolt	x	x	x	x
293/4250					260					PVM-064																			C	2450	SAE "C" 2/4-Bolt	x	x	x	x
400/5800			350							PVWH-25																			C	2400	SAE "C" 2-Bolt	x	x	x	x
400/5800			350							PVG-065																			B	2700	SAE "B" 2/4-Bolt	x	x	x	x
293/4250					260					PVM-076																			C	2450	SAE "C" 2/4-Bolt	x	x	x	x
275/4000						240				PVWH-34																			C	2400	SAE "B" 2-Bolt	x	x	x	x
293/4250										PVG-075																			B	2700	SAE "B" 2/4-Bolt	x	x	x	x
293/4250					260					PVM-098																			C	2450	SAE "C" 2/4-Bolt	x	x	x	x
210/3000								175		PVWH-45																			C	2400	SAE "C" 2-Bolt	x	x	x	x
400/5800			350							PVG-100																			C	2400	SAE "C" 2-Bolt	x	x	x	x
293/4250					260					PVM-130																			C	2450	SAE "C" 2/4-Bolt	x	x	x	x
140/2000								105		PVWH-60																			C	1800	SAE "C" 2-Bolt	x	x	x	x
293/4250					260					PVG-130																			C	2400	SAE "C" 2-Bolt	x	x	x	x
400/5800			350							PVK-140																			D	1800	SAE "D" 4-Bolt	x	x		x
450/6500		420								PVV-200																			E	2200	SAE "E" 4-Bolt	x	x	x	x
400/5800			350							PVV-250																			E	2200	SAE "E" 4-Bolt	x	x	x	x
400/5800			350							PVK-270																			F	1500	SAE "F" 4-Bolt	x	x		x
275/4000						240				PVK-370																			F	1500	SAE "F" 4-Bolt	x	x		x
500/7250	450									PVV-440																		-	1500	ISO 250 4-Bolt	x	x	x	x	
400/5800			350							PVV-540																			-	1500	ISO 250 4-Bolt	x	x	x	x

- PVM CompactLow Noise Design
- PVWH Pumps for Mobile and Industrial Applications
- PVG Compact High Response Pumps
- PVK Pumps for Industrial Applications
- PVV Pumps for Industrial Applications

### additional oilgear pumps

- PVWW Pumps for Low Viscosity
- PVWC Closed Loop Pumps
- PF 14,500 psi Fixed Displacement Pumps